| | | | , |
|-------------|-------------|---------------|---|
| Qty -041 | Qty -043 | Part Number | Description |
| Х | | D4362-041 | SKIDTUBE ASSEMBLY |
| | X | D4362-043 | SKIDTUBE ASSEMBLY |
| 1 | 1 | D2600-1-240 | EXTRUSION |
| 1 | 1 | D2646 | AFT CAP |
| 12 | 12 | D2649 | CROSS BOLT SPACER |
| 14 | 39 | D3275-1 | CROSS BOLT SPACER |
| 1 | 1 | D3282-041 | FLOAT WEB |
| 1 | 1 | D3285-1 | CAP |
| 24 | 24 | D3411-3 | WASHER |
| 1 | 1 | D3413-1 | RING |
| 1 | 1 | D3415-041 | NUT PLATE |
| 20 | 20 | D3873-3 | BUSHING |
| 8 | 8 | D3904-1 | WASHER |
| 1 | 1 | D4368-041 | FWD WEARPLATE ASSY |
| 1 | 1 | D4368-043 | AFT WEARPLATE ASSY |
| 1 | 1 | D4383-1 | WEARPAD |
| 1 | 1 | D4383-3 | WEARPAD |
| 8 | 8 | ALS7-1032-130 | INSERT (or AKS4-1032-130, ALS4-1032-130, AELS-1032-130) |
| 2 | 2 | AN3C36A | BOLT |
| 2 | 2 | AN3C37A | BOLT |
| 6 | 6 | AN3C40A | BOLT |
| 10 | 10 | AN3C4A | BOLT |
| 1 | 1 | AN4C5A | BOLT |
| 2 | 2 | CCR264SS3-3 | RIVET |
| 2 | 2 | CR3212-4-03 | RIVET |
| 10 | 10 | MS21043-3 | NUT |
| 8 | 8 | NAS1149C0332R | WASHER (OR AN960C10L) |
| 2 | 2 | NAS1149C0363R | WASHER (OR AN960C10) |
| 1 | 1 | NAS1149C0463R | WASHER (OR AN960C416) |
| 2 | 2 | NAS1515H3L | WASHER |

NOTES:

- 1) MATERIAL: N/A
- 2) FINISH: CHEMICAL CONVERSION COAT PER DART QSI 005 4.1 PRIOR TO INSTALLING D3282-041 WEB
 - PRIME (REF 4.2.1.3.3) AND PAINT WHITE PER DART QSI 005 4.2
 - BLACK ANTI-SKID PAINT AS INDICATED TO 0.5" ABOVE LOCATION RIDGE PER DART QSI 005 4.4
- C

- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: NONE
- 7) WEIGHT: D4362-041 = 54.0 LBS D4362-043 = 54.3 LBS
- 8) WELD PER DART QSI 004
- 9) ALL HOLES DRILLED ON CENTERLINES.
- 10) DAMAGE TOLERANCE ON FWD BEND:

THERE SHOULD BE NO VISIBLE WRINKLES IN THE BEND FROM THE GROUND TO A HEIGHT OF 7 INCHES ABOVE THE GROUND. IT IS ACCEPTABLE TO POLISH OUT GOUGES UP TO 0.020 DEEP IN THE BENT PORTION OF THE TUBE. A MAXIMUM REDUCTION IN DIAMETER OF 0.150" IS ACCEPTABLE IN THE BENT PORTION OF THE TUBE.

- 11) BOND D3282-041 FLOAT WEB INTO D4362-041/-043 OUTER TUBE WITH NON-STRUCTURAL SIKAFLEX-241/291 ADHESIVE PER DART QSI 015. ENSURE HOLES LINE-UP.
- 12) DRILL Ø0.297 HOLES FOR ALS7-1032-130 INSERTS USING DT4362-1T2 BEFORE FINISH.
 INSTALL ALS7-1032-130 INSERTS AFTER FINISH. SEAL WEARSHOE BOLTS WITH SIKAFLEX-241/-291.
- 13) COAT ALL EXPOSED FASTENERS WITH LPS LABORATORIES "LPS PROCYON" AFTER FINAL ASSEMBLY, CLEAN OFF EXCESS GREASE WITH WASH 'N WIPE DEGREASER.



| С | REVISI | E NOTE 2: ADE | ANTI-SKID PAINT | DB | 14.04.15 | |
|--|--------|---------------|---|--------------|----------|--|
| B REVISE NOTE 2: FINIS WAS POWDERCOAT, | | | SH NOW PRIME/PAINT , REF. PAR13-256 | DW | 13.05.17 | |
| A NEW ISSUE | | | | sc | 11.05.05 | |
| REV. | D | | DESCRIPTION | BY | DATE | |
| DESIGN | | SC | DART AEROSPACE USA, INC | | | |
| DRAWN | | DB | KENT, WA | | | |
| CHECKED | | DW | DRAWING NO. | | REV. C | |
| MFG. APPR. | | J. | D4362 | SHEET 1 OF 4 | | |
| APPROVED | | Man | TITLE | | SCALE | |
| DE APPR. | | -# | 206L/407 SKIDTUBE ASSEMBLIES NTS | | | |
| DATE | 14.0 | 4.15 | COPYRIGHT © 2011 BY DART AEROSPACE USA, INC THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC. | | | |

7

(

.5

3

2

1





